

**SAFETY DATA SHEET**  
according to 830/2015/EC, 28.05.2015



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

**1. Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name	<b>PIPE SEALER PTFE 5572</b>
Article number	A-228
	A-683
	A-676

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

identified uses	Anaerobic sealant designed for sealing tube connections in gas and central heating installations.
uses advised against	-

**1.3. Details of the supplier of the safety data sheet**

Manufacturer	NALMAT-Trzebinia Marian Krzyworzeka ul. Kościuszki 88 32-540 Trzebinia tel. +48 32 612 10 10 fax. +48 32 612 10 66 <a href="http://www.technicqll.pl">www.technicqll.pl</a> <a href="mailto:office@technicqll.pl">office@technicqll.pl</a> <a href="mailto:jakosc@technicqll.pl">jakosc@technicqll.pl</a>
--------------	--

**1.4. Emergency telephone number:**

+ 48 (032) 711 53 27 during normal office hours - Monday - Friday 6.00am - 2.00pm  
112

**2. Hazards identification**

**2.1. Classification of the substance or mixture**

Human health hazards:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.
Environmental hazards:	Harmful to aquatic life with long lasting effects
Physical and chemical hazards:	-

**2.2. Label elements**

Contains:  $\alpha,\alpha$ -dimethylbenzyl hydroperoxide (No. EC: 201-254-7) and ethyl methacrylate (No. EC: 202-597-5). May cause occurring allergic reaction.

Warning symbol:



**DANGER**

H315 – Causes skin irritation.  
H317 – May cause an allergic skin reaction.  
H318 – Causes serious eye damage.  
H319 – Causes serious eye irritation.  
H332 – Harmful if inhaled.  
H335 – May cause respiratory irritation.  
H412 – Harmful to aquatic life with long lasting effects.

**SAFETY DATA SHEET**  
according to 830/2015/EC, 28.05.2015



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

P102 – Keep out of reach of children.  
P302+P352 – IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 – Immediately call a POISON CENTER or doctor/physician.  
P280 – Wear protective gloves/protective clothing/eye protection/face protection.  
P501 – Dispose of contents/container to a mine waste dump.

**2.3. Other hazards**

PBT - lack of information concerning fulfilment of the criteria in accordance with annex XIII of Reach Directive.  
vPvB - lack of information concerning fulfilment of the criteria in accordance with annex XIII of Reach Directive.

**3. Composition/information on ingredients**

**3.1. Substance: -**

**3.2. Mixtures**

Description	CAS	UE	REACH	Content %	Classification
$\alpha,\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	201-254-7	01-2119475796-19-0002	<5%	Org. Perox. EF H242, Acute Tox. 3, H331, Acute Tox. 4, H312, Acute Tox. 4, H302, Skin Corr. 1B, H314, STOT RE. 2, H373, Aquatic Chronic 2, H411. (For c<5%: Acute Tox.4, H332, STOT SE.3, H335, Skin Irrit.2, H315, Eye Dam.1, H318, Aquatic Chronic3, H412)
N,N-dimethyl-p-toluidine	99-97-8	202-805-4	01-2119937766-23-0000	0-0,5	Acute Tox.3, H331, H311, H301 STOT RE.2, H373, Aquatic Chronic3, H412
cumene	98-82-8	202-704-5	01-2119473983-24-0015	0-05	Flam.Liq.3, H226, Asp. Tox.1, H304 STOT SE.3, H335 Aquatic Chronic 2, H411
ethyl methacrylate	97-63-2	202-597-5	01-2119490215-40-0002	30-40	Flam. Liq.2, H225, Eye Irrit.2, H319 STOT SE.3, H335, Skin Irrit.2, H315 Skin Sens.1, H317

**SAFETY DATA SHEET**  
**according to 830/2015/EC, 28.05.2015**



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

**4. First aid measures**

**4.1 Description of first aid measures**

After eye contact	Rinse immediately with plenty of water at least 15 minutes.. Lift eyelids and rinse thoroughly underneath them. If irritation persists, contact a physician.
After skin contact	wash skin with warm water and soap. In case of skin irritation seek medical attention.
After inhalation	fresh air and rest if symptoms persist seek medical attention.
After swallowing	rinse mouth with plenty of water and seek medical attention. Show the package or label.

**4.2. Most important symptoms and effects, both acute and delayed**

Not available

**4.3. Indication of any immediate medical attention and special treatment needed**

The decision of the method of further procedure should be made by a doctor after exact assessment of victim's conditions.

**5. Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media CO<sub>2</sub>, foam extinguisher, water jet.  
Unsuitable extinguishing measures: strong water jet.

**5.2. Special hazards arising from the substance or mixture**

Irritating organic vapours may be formed.

**5.3. Advice for firefighters**

Handling in case of a fire:  
Inform the neighbourhood about a fire. Remove all persons from an exposure area not taking part in liquidation of the fire. Inform the fire brigade and police. Containers exposed to action of a fire or high temperatures should be cooled with water from safe distance.  
Special protective equipment: protective clothes and self-contained breathing apparatus.

**6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

For persons not belonging to the staff removing the results of accident: Limit access of outsiders to the accident area until cleaning operation is finished. Avoid pollution of eyes and skin. Ensure good ventilation.  
For person liquidating results of accident: Make sure that damage repair and its effects are carried out only by a well trained staff.

**6.2. Environmental precautions:**

Don't allow to enter soil, sewage system, surface or ground waters.

**6.3. Methods and material for containment and cleaning up:**

In case of spilling wipe or scrape or cover and blend with inert material (sand) and take up mechanically in suitable containers adding water in order to cure. Disposal in accordance with local regulations.

**6.4. Reference to other sections**

Information concerning safe handling – section / chapter 7.  
Information concerning personal protective equipment - section / chapter 8.  
Information concerning utilisation - section / chapter 13.

**SAFETY DATA SHEET**  
according to 830/2015/EC, 28.05.2015



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

**7. Handling and storage**

**7.1. Precautions for safe handling:**

Ensure a good ventilation in a work place. Avoid spilling. Avoid contamination of skin and eyes. Prolonged and repeated breathing of the vapours may cause irritation of inhalation system. Avoid contamination of skin. May cause sensitiveness at allergic persons.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep in cold, dry and well ventilated work place in tightly closed containers between 5°C - 25°C. Keep away from food. Keep out of direct sunlight. The lower temperature of storage the longer durability of the adhesive. Do not keep near sources of ignition. Do not smoke.

**7.3. Specific end use(s)**

No data.

**8. Exposure controls/personal protection**

The personal protection media should fulfil the requirements of instructions of the Cabinet of 21.12.2005 (Dz. U. No. 259, pos. 2173) Directive 89/686/WE (together with later changes). The employer is obliged to ensure measures of personal protection suitable for activities that are made and their cleaning and maintenance.

**8.1. Control parameters**

cumene

NDS 100 mg/m<sup>3</sup>

NDS<sub>I</sub>H 250 mg/m<sup>3</sup>

**8.2. Exposure controls**

**Breathing equipment:**

No special protection is required, one should not breathe the product vapours.

**Protection of hands:**

No special protection is required, but in order to minimize risk, it is recommended to use gloves and protective clothing and work boots.

**Eye protection:**

No special protection is required, but in order to minimize risk, it is recommended to use protective glasses.

**Protection of body:**

Working clothes.

**9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Psychical state	High viscosity liquid
Colour	White/creamy
Boiling point	-
Ignition point	> 125°C
Odour	Characteristic
Solubility in water	insoluble
Solubility in ketones and esters	-
Density at 25°C	28000 – 77000 mPa*s

**9.2. Other information**

Lack of additional tests.

**SAFETY DATA SHEET**  
according to 830/2015/EC, 28.05.2015



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

**10. Stability and reactivity**

**10.1. Reactivity**

No data.

**10.2. Chemical stability**

The product is stable in normal conditions of storage, handling and use.

**10.3. Possibility of hazardous reactions**

Reactions with strong oxidizing agents.

**10.4. Conditions to avoid**

Avoid contacts with water and alkaline materials. Danger of polymerization may occur if the adhesive is mixed with amines or water. The component does not decompose if it is stored in accordance with the recommendations.

**10.5. Incompatible materials**

No data.

**10.6. Hazardous decomposition products**

Do not occur if the material is stored properly.

**11. Toxicological information**

**11.1. Information on toxicological effects**

on the skin:	Possible irritation of skin (degreasing, inflammation).
on the eye:	Possible irritation of eyes.
after swallowing:	-
after inhalation	-

**12. Ecological information**

**12.1. Toxicity**

No data.

**12.2. Persistence and degradability**

No data.

**12.3. Bioaccumulative potential**

Possess potential for bioaccumulation.

**12.4. Mobility in soil**

Easily absorbed in soil.

**12.5. Results of PBT and vPvB assessment**

PBT	Lack of information concerning fulfilment of criteria in accordance with Annex XIII of Reach Directive.
vPvB	Lack of information concerning fulfilment of criteria in accordance with Annex XIII of Reach Directive.

**12.6. Other adverse effects**

The product does not dissolve in water. Avoid penetration of the product into sewage system and ground water. Harmful to aquatic organism the aquatic environment.

**SAFETY DATA SHEET**  
according to 830/2015/EC, 28.05.2015



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

**13. Disposal considerations**

**13.1. Waste treatment methods**

Product waste: cover the arisen waste an absorptive material e.g. sand, diatomaceous earth, sawdust – take up and collect in closed containers and undergo neutralization in accordance with local and state regulations.

Packaging waste: completely empty the packaging and transfer to specialized firm to recuperate or recycling the material.

Waste code:

**08 04 09** Waste adhesives and sealants contain no organic solvents or other dangerous substances.  
**15 01 10** Packaging containing residues of dangerous substances or contaminated with them.

**EU Legal Instruments**

Directives of European Parliament and Council 2006/12/EC and 94/62/EC ,Directive of Council 91/689/EEC

**State Legal Instruments**

**14. Transport information**

**14.1. UN-Number:**

The product is not regarded as dangerous. It is not subject to RID/ADR regulations It can be transported in any means of transport in hermetically closed packages.

**Land transport ADR/RID and GGVSEB** Class ADR/RID – GGVSEB:

(international/state)

**Sea transport IMDG/VSee:** -

**Air transport ICAO – TI I IATA – DGR:** -

**14.2. Proper shipping name**

Not applicable.

**14.3. Transport hazard class(es)**

Not applicable.

**14.4. Packing group**

Not applicable.

**14.5. Hazards to environment**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

**14.6. Special precautions for user**

While handling the cargo, apply personal protection measures according to section 8.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

**15. Regulatory information**

**15.1. Legislation related to safety, health and environment protection specific for substance or mixture:**

The regulation of European Parliament and Council (EC) no. 1907/2006 of 18 December 2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH), for establishing the European Chemical Agency, changing the directive 1999/45/EC and cancelling the regulation of EEC) no.793/93 and the regulation of Committee(EC) no.1488/94, as well as the directive of council 76/769/EEC and the directives of

**SAFETY DATA SHEET**  
**according to 830/2015/EC, 28.05.2015**



Date: 2011-05-19  
Update: 2017-01-21

**PIPE SEALER PTFE**

Committee 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC,  
The regulation of European Parliament and Council (EC ) no.1272/2008 of 16 December 2008 concerning the classification, labeling and packing the substances and mixtures, changing and cancelling the directives 67/548/EEC and 1999/45/EC and changing the regulation ( EC ) no.1907/2006  
The regulation of Committee ( EC ) no.790/2009 of 10 August 2009 adopting to the scientific and technological progress the regulation of European Parliament and Council (EC) no 1272/2008 of 16 December 2008 concerning the classification, labeling and packing the substances and mixtures  
The regulation 453/2010/EU Council of 10.05.2010 changing the regulation no. 1907/2006/EU of European Parliament and Council concerning the registration, estimation, granting permissions and suitable limits in the range of chemicals ( REACH )  
The directive of European Parliament and Council no.2006/12/EC of 5 April 2006 concerning waste.  
The directive of Council no. 91/689/EEC of 12 December 1991 concerning dangerous waste.  
The directive of European Parliament and Council no 94/62/EU. of 20 December 1994 concerning packaging and packaging waste.

**15.2. Estimation of chemical safety:**

-

**16. Other information**

Explanation of symbols in the 3 point of Safety Data Sheet:

H225 – Highly flammable liquid and vapour  
H315 – Causes skin irritation  
H335 – May cause respiratory irritation  
H317 – May cause an allergic skin reaction  
H319 – Causes serious eye irritation  
H314 – Causes severe skin burns and eye damage  
H312 – Harmful in contact with skin  
H302 – Harmful if swallowed  
H242 – Heating may cause a fire  
H331 – Toxic if inhaled  
H373 – May cause damage to organs through prolonged or repeated exposure  
H411 – Toxic to aquatic life with long lasting effects  
H332 – Harmful if inhaled  
H311 – Toxic in contact with skin  
H318 – Causes serious eye damage  
H412 - Harmful to aquatic life with long lasting effects  
H301 – Toxic if swallowed  
H226 – Flammable liquid and vapour  
H304 – May be fatal if swallowed and enters airways  
Org. Perox. EF – Organic peroxide  
Acute Tox. 3 – Acute toxicity category. 3  
Acute Tox. 4 – Acute toxicity category. 4

Skin Corr. 1B – Corrosive action on skin. 1  
STOT RE. 2 – Acts toxically on destination organs. 2  
Aquatic Chronic 2 – Create hazard for aquatic environment category. 2  
Aquatic Chronic 3 – Create hazard for aquatic environment category. 3  
STOT SE.3 – Acts toxically on destination organs. 3  
Skin Irrit.2 – Irritating to skin category. 2  
Eye Dam.1 – Serious damage of eyes category. 1.  
Flam.Liq.3 – Inflammable liquid substance category. 3  
Flam.Liq.2 – Inflammable liquid substance category. 2  
Asp. Tox.1 – Hazard caused by aspiration category. 1

**SAFETY DATA SHEET**  
**according to 830/2015/EC, 28.05.2015**



Date: 2011-05-19  
Update: 2017-01-21

---

**PIPE SEALER PTFE**

---

Eye Irrit.2 – Irritating to eyes category. 2  
Skin Sens.1 – Irritating to skin category. 1.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**MSDS developed by NALMAT Trzebinia**